# **A-40SS Airless Foamer**

**MODEL: AF 912905** 

#### **OVERVIEW**

The A-40SS Airless Foamer is a medium volume foam applicator for projecting foaming chemicals on to any surface up close or at distances up to 10 feet without compressed air. This venturi injection system uses boosted water pressure (125 - 350 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. The solution then flows through the discharge hose and trigger gun to the "airless" foam wand which draws in atmospheric air to create and project wet, clinging foam.

#### **Key Features**

- No compressed air required
- Designed for foam cleaning medium to large sized areas
- Projects wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Projects foam up to 10' (depending on water pressure)
- Chemically resistant components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available as a portable system with a stainless steel cart assembly

#### **Includes**

- Stainless steel mounting bracket
- Stainless steel inlet ball valve
- Machined stainless steel injector body
- Machined stainless steel airless foam wand
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose & trigger gun

#### **Options**

Large Stainless Steel Hose Rack	# 224150
Stainless Steel Jug Racks	
Jug Rack, SS, 1 Gallon, Round/Square	# 224200
Jug Rack, SS, 2 1/2 Gallon	# 224210
Jug Rack, SS, 5 Gallon	# 224215
<b>Lid &amp; Suction Hose for 1 &amp; 5 Gallon Pails</b> Pail Lid Suction Hose Assembly	# 709101
Alternate Check Valve - EPDM Standard Check Valve, Chemical, SS, Viton, 1/4"	# 491324-V

## **APPLICATIONS**

- Food & Beverage
- Agriculture/Horticulture
- Vehicle Wash
- Dairy
- Industrial
- Paper Mill
- Pharm/Bio
- And Many Other Applications!



## REQUIREMENTS

### **Chemical Concentrate**

## Water

 Temperature
 up to 180°F

 Pressure
 125 - 350 PSI

 Flow
 2.84 GPM @ 250 PSI

 Supply Line
 1/2"

**Hose** 3/8" x 50'

Nozzle A 41SS Airless Foam Wand

