

Pump-Up Bullet™ Foamer Pro, 3 Gallon

MODEL: AF 925008

OVERVIEW

The 3 Gallon Pump-Up Bullet™ Foamer Pro is a portable foam applicator for applying pre-diluted, foaming chemicals to any surface as wet, clinging foam. This professional model features a heavy-duty hose, trigger gun, and extension wand and combines the many advantages of foam cleaning with the familiar ease and portability of a typical pump-up sprayer. Use the compressed air "quick charge" valve to eliminate pumping. The adjustable Bullet™ foam nozzle draws in atmospheric air to create a wet, clinging foam and projects a wide pattern or narrow stream.

Key Features

- Combines the advantages of foam application with the familiar ease and portability of a pump-up sprayer
- Use the "quick charge" valve to pressurize with an air compressor instead of pumping
- Creates a wet, clinging foam that increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Just fill the tank with ready-to-use chemical solution, pump it up and foam!
- Easy-grip trigger gun with locking latch and extended wand
- Adjustable Bullet™ foam nozzle projects a wide fan pattern for fast coverage or a narrow stream for increased range

Includes

- Heavy-duty 3 gallon HDPE tank with UV inhibitor
- Heavy-duty manual pump
- Viton seals and O-Rings (EPDM available)
- Pressure relief valve
- Compressed air "quick charge" valve
- Heavy-duty trigger gun and 6' discharge hose
- Extended wand and adjustable Bullet™ nozzle

Options

Repair Kit

O Ring & Seal Repair Kit (Viton)	# 709040
O Ring & Seal Repair Kit (EPDM)	# 709040-E

Proportioning / Filling Options

1-Way Ball Valve Mixing Station (4 GPM)	# 985100
1-Way Push Lever Mixing Station (4 GPM)	# 981100



APPLICATIONS

- Animal Facility Sanitation
- Insecticides & Herbicides
- Agriculture/Horticulture
- Vehicle Wash
- Food & Beverage
- Hood & Vent
- Janitorial/Sanitation
- Pharm/Bio
- School Hygiene
- Supermarkets
- And Many Other Applications!

REQUIREMENTS

RTU Chemical Solution

Temperature	up to 120° F
Pressure	up to 45 PSI

AFCO
equipment & engineering