

Pump Fed XV Foamer

MODEL: AF 919305

OVERVIEW

The Pump Fed XV Foamer is a high volume foam applicator for projecting ready-to-use foaming chemicals on to any surface up close or at distances up to 15 feet with the fan nozzle. This unit receives ready-to-use chemical solution from a central chemical feed system and creates rich, clinging foam by injecting compressed air into the solution to greatly increase volume and coverage ability. A high volume of foam is then projected through the discharge hose and fan nozzle. Order the optional zero degree nozzle for increased throw distance.

Key Features

- Receives ready-to-use chemical solution from a central chemical feed system
- Designed for foam cleaning large surfaces and areas
- Projects a high volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 15' range)
- Covers up to 500 sq ft (46.5 sq m) in 1 minute
- Adjustable foam consistency (wet/dry)
- Chemically resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments

Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene foamer body
- 50' hose, polypropylene foam wand & fan nozzle

Options

Large Stainless Steel Hose Rack	# 224150
Optional Zero Degree Nozzle Nozzle, NPB, 3/4" - 00400	# 180154
Recommended Foam Solution Check Valves & Strainer	
Check Valve, PP, 1/2" (EPDM)	# 491409
Check Valve, PP, 1/2" (Viton)	# 491411
SS "Y" Strainer	# 150350
Alternate Air Check Valve - EPDM Standard	
Check Valve, Air, SS, 1/4" MM (Viton / Hast)	# 491306

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Paper Mill
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Ready-to-Use Chemical Solution (Minimum 35 PSI at the Unit)

Temperature	up to 160°F
Pressure	35 - 100 PSI
Flow	4 GPM @ 40 PSI
Supply Line	1/2"

Compressed Air

up to 6 CFM

Hose

1" x 50'

Nozzle

50400

AFCO
equipment & engineering