

W-20 Spray-All

MODEL: AF 970220

OVERVIEW

The W-20 Spray-All is a water-driven, low volume spray applicator for applying chemical solutions to a variety of surfaces. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a light, uniform spray. With a flow rate of just under 1 gallon per minute, this unit is great for spraying virtually any sized area or object slowly and completely with very little run-off.

Key Features

- Creates a low volume spray (under 1 GPM @ 40 PSI)
- Ideal for precision application in small areas and near sensitive equipment where minimal over-spray is crucial
- Fan pattern nozzle for even coverage
- Chemically resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Use it anywhere 35-125 PSI water is available
- Available as a "high concentrate" unit capable of creating strong dilution ratios for tough cleaning jobs

Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle

Options

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

- 1 Gallon Round/Square # 224200
- 1 Gallon Round/Square Locking # 224200-L
- 2 ½ Gallon (8 ½" x 10 ½") # 224210
- 5 Gallon (12" x 12") # 224215
- 5 Gallon Round Locking # 224216

Lid & Suction Hose for 1 & 5 Gallon Pails

Pail Lid Suction Hose Assembly # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315



APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Military
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 160°F
Pressure	35 - 125 PSI
Flow	0.84 GPM @ 40 PSI
Supply Line	1/2"

Hose

1/2" x 50'

Nozzle

2520

AFCO
equipment & engineering