

315 Sanitizer

MODEL: AF 973650

OVERVIEW

The 315 Sanitizer is a high volume venturi injection system that uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create the lean ratios required for no-rinse sanitizing in food plants. The solution is then projected through the discharge hose and fan nozzle as a 4 GPM coarse spray on to any surface or object.

Key Features

- Creates a high volume, coarse spray
- Dilutes concentrated sanitizers to the lean ratios required for no-rinse applications in food plants
- Projects a high volume flooding spray in a fan pattern for complete coverage
- Chemically resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments

Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene injector body
- 20 color-coded metering tips to set dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle

Options

| | |
|--|----------|
| Large Stainless Steel Hose Rack | # 224150 |
| Stainless Steel Jug Racks | |
| 2 ½ Gallon (8 ½" x 10 ½") | # 224210 |
| 5 Gallon (12" x 12") | # 224215 |
| 5 Gallon Round Locking | # 224216 |
| Lid & Suction Hose for 1 & 5 Gallon Pails | |
| Pail Lid Suction Hose Assembly | # 709101 |
| Alternate Sanitizer Check Valve - Viton Standard | |
| Check Valve, Chemical, PP/EPDM, 1/4" | # 491311 |

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

| | |
|-------------|----------------|
| Temperature | up to 160°F |
| Pressure | 35 - 125 PSI |
| Flow | 4 GPM @ 40 PSI |
| Supply Line | 1/2" |

Hose

1/2" x 50'

Nozzle

40100

AFCO
equipment & engineering